



Committing to the future

The simple and flexible solution for monitoring measurement data

Automated with **testo Saveris™**.



testo Saveris Software™

Start Edit Options Template Style

Copy Paste Clipboard

Open New group Day Month Delete Edit Evaluation View

Original size

Group 0
Group 1

Data

Alarms

System

Reports

| Time | Temp 1 (°C) | Temp 2 (°C) |
|---------------------|-------------|-------------|
| 10.10.2007 00:00:00 | 19.5 | 16.5 |
| 10.10.2007 01:00:00 | 18.5 | 16.5 |
| 10.10.2007 02:00:00 | 17.5 | 16.5 |
| 10.10.2007 03:00:00 | 17.0 | 16.5 |
| 10.10.2007 04:00:00 | 16.5 | 16.5 |
| 10.10.2007 05:00:00 | 16.0 | 16.5 |

October 2007
M T W T F S S
1 2 3 4 5 6 7
8 9 10 11 12 13 14
15 16 17 18 19 20 21
22 23 24 25 26 27 28
29 30 31

November 2007
M T W T F S S
1 2 3 4
5 6 7 8 9 10 11
12 13 14 15 16 17 18
19 20 21 22 23 24 25
26 27 28 29 30

December 2007
M T W T F S S
1 2
3 4 5 6 7 8 9
10 11 12 13 14 15 16
17 18 19 20 21 22 23
24 25 26 27 28 29 30
31

Saveris

Anmeldung

Rechner Converter

Fühler
404 500
505 600

2 - G (1st/2nd)

Enter

Exit

OK

Cancel

Back

Forward

Home

Power

Status Free

testo Saveris™ System overview

testo Saveris radio probe

Probe versions with internal and external temperature and humidity sensors allow the adaptation to every application. The radio probes are available with or without a display as an option. The memory in the probe ensures that the measurement data is not lost in the event of an interference in the radio link. Current measurement data, the battery status and the quality of the radio link are shown in the display.



testo Saveris radio probe



testo Saveris radio probe

testo Saveris radio probe

testo Saveris base

The base is the heart of testo Saveris and can save 40,000 readings independent of the PC. This corresponds to around one year of 15 minutes. The system data and alarms are visible via the display of the Saveris base.



testo Saveris base



testo Saveris router

testo Saveris software

The testo Saveris software offers simple operation and an intuitive user interface. The Saveris software is available in two different versions: as the basic version SBE (Small Business Edition) or the PROF (Professional) software version with diverse additional options. If external access to the measurement data from outside the location is required, Internet access for the display of all measurement data can be set up.



testo Saveris software

USB or Ethernet

Expansion via Ethernet probe possible

Further system possibilities

In addition to the radio probes, probes can be used that are directly connected to the Ethernet. The existing LAN infrastructure can be used through this.

A network-compatible version of the Saveris software is also available. Further information on this is available from testo or from selected specialist retailers.

Please contact us for more information.