

testo Saveris™ System overview

testo Saveris™ wireless probe

Probes are available with internal and external temperature and humidity sensors and easily adapt to any application. Wireless probes are available with or without an optional display. Current measurement data, battery status, and signal strength are shown in the display. Each probes' memory ensures that measurement data is never lost in the event of an interruption in the wireless link.



testo Saveris™ wireless probe



testo Saveris™ wireless probe

testo Saveris wireless probe

testo Saveris™ base

The base is the heart of testo Saveris™ and can save 40,000 readings independent of the PC. This corresponds to approximately one year of memory capacity at a measuring rate of 15 minutes. The system data and alarms are visible in the display of the Saveris™ base.



testo Saveris™ base



testo Saveris™ router

testo Saveris™ software

testo Saveris™ software offers simple operation and an intuitive user interface. Saveris™ software is available in two different versions: as a basic version SBE (Small Business Edition) or a PROF (Professional) software version with valuable extra features. If external access to data is required, Internet access can be easily set up.



testo Saveris™ software

USB or Ethernet

Expansion via Ethernet probe possible

More system possibilities...

In addition to the wireless probes, ethernet capable probes are also available. An existing LAN infrastructure can be utilized for this.

A network-compatible version of Saveris™ software is also available. Contact testo for additional information.

Please contact us for more information.

testo Inc · 40 White Lake Rd., Sparta, NJ 07871
 800-227-0729, Phone: 862-354-5001, Fax: 862-354-5020
 e-mail: info@testo.com · www.testo.us